

DM-1: In-Line Dual TDS Monitor

Measure the tap water coming in vs. the purified water going out of your water filtration system at any time.

FEATURES

- Displays TDS levels of the feed water and product water with in & out electrode probes.
- Highly efficient and accurate due to its advanced microprocessor technology.
- Auto-Off function conserves battery power. The unit shuts off automatically after 10 minutes of non-use.
- Dual Range 0-9990 ppm (From 0 - 999 ppm the resolution is 1 ppm. From 1000 to 9990 ppm, the resolution is 10 ppm, indicated by a blinking 'x10' image.)
- Factory Calibrated: our meters are calibrated with a 342 ppm NaCl solution. Meters can be recalibrated with a mini-screwdriver.
- Comes equipped with John Guest Quick-Connect T-fittings as shown.
- Installs quickly and easily.



SPECIFICATIONS

Range:	0-9990 ppm
Accuracy:	±2%
Cable Length:	24.5" (including sensor)
Fittings:	1/4" standard, also available with 3/8" or 1/2"
Power source:	2 x 1.5 V button cell batteries (included)
Battery life:	approx. 1000 hours of continuous use
Size:	7.6 x 2 x 4.7 cm (3 x .8 x 1.9 in.)
Weight:	79.4 g (2.8 oz.)



Use the monitor to determine when the filters need to be changed