

## UV // Tap Plus



Powered by  
**Sterilight**

- Compact point-of-use (single tap) UV disinfection system for recommended flow rates up to 3 gpm (11 lpm)
- Features "count down" timer display and lamp change reminder

### IMPROVED WARRANTY

PART NUMBERS	
N. America (NEMA P-15)	S2Q-PA
EU CEE (CEE 7/7)	S2Q-PA/2
AUS/NZ (AS 3112)	S2Q-PA/2A
UK (BS 1363)	S2Q-PA/2B
DISINFECTION FLOW RATES	
Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)	
16 mJ/cm <sup>2</sup>	5 GPM (18 lpm) (1.1 m <sup>3</sup> /hr)
30 mJ/cm <sup>2</sup>	3 GPM (11 lpm) (0.7 m <sup>3</sup> /hr)
40 mJ/cm <sup>2</sup>	2 GPM (8 lpm) (0.4 m <sup>3</sup> /hr)
SPECIFICATIONS	
Dimensions in ch (cm)	17" x 2 1/2" (43.6 cm x 6.5 cm)
Shipping Weight lbs (kg)	7 lbs (3.2 kg)
Connection Size	1/2" MNPT
Power Consumption	22W
REPLACEMENT PARTS	
Lamp/Quartz Sleeve Kit	S330-QL
UV Lamp Only	S330RL
Quartz Sleeve Only	QS-330
Controller	BA-ICE-S
Sediment Cartridge	--
Carbon Cartridge	--